

Kilslidventil

KLA-048

Gate Valve

KLA-048

ASA-Kilslidventil
KLA-048

Material A105N
Storlek 1/2" till 2 1/2"
Tryckklass 800 lbs

DESIGN - STANDARD

- Design och tillverkning: API 602
- Bygglängd: Tillverkarens standard
- Insticksvetsändar "Socket Weld": ASME/ANSI B16.11
- Tryck & Temperaturklass: ASME/ANSI B16.34
- Provtryckning: API 598
- Massiv kilslid



ASA-Gate Valve
KLA-048

Material A105N
Size 1/2" to 2 1/2"
Pressure 800 lbs

DESIGN - STANDARDS

- Design and manufacture: API 602
- Face to face: Manufacturers standard
- Socket Weld Ends: ASME/ANSI B16.11
- Pressure Temperature Rating: ASME/ANSI B16.34
- Pressure Test: API 598
- Solid Wedge

MATERIAL

Denomination	Benämning	Material
Body	Hus	A105N
Seats	Säte	A105+STL
Wedge	Kilslid	A276-420
Bonnet	Överdel	A105N
Stem	Spindel	A276-410
Gasket	Tätning	SS304+Graphit
Packing	Packning	Graphit
Hexagon screw	Sexkantsskruv	A193 B7

MÅTTUPPGIFTER / DIMENSIONS

DN	Size	d	S	l1	l	w	h	h/open	varv/turns	kg
15	1/2"	10	21.8	9.7	79	100	145	160	3.5	2.3
20	3/4"	13	27.1	12.7	92	100	150	165	4	2.5
25	1"	18	33.8	12.7	111	120	180	200	5	4.4
40	1 1/2"	29	48.7	12.7	120	160	210	250	5.5	7.2
50	2"	36.5	61.1	15.9	140	180	250	285	6.5	11
65	2 1/2"	-	74.7	19	-	180	290	320	-	15

